

Product Name **PET50(A) PAT1 8LK**  
 ID: 0844598F8

## Application/Features

- Permanent type adhesive
- For common label applications
- UL/CUL Recognized Product UL No. 3755BZ50

## Product Construction

Face Stock	: Polyester film. (Clear • With top coating)
Adhesive	: Acrylic type adhesive.
Release Liner	: Glassine paper, one side is polyethylene laminated. (Blue)

## Properties

Item		Value	Test Method
Thickness	Face Stock (μm)	<b>50</b>	JIS-C-2318
	Liner (μm)	<b>88</b>	JIS-P-8118
Adhesion	After 30min. (N/25mm)	<b>13.0</b>	LINTEC Method
	After 24 hrs. (N/25mm)	<b>16.0</b>	
Holding Power (Sec.)		<b>NC 30000</b>	
Ball Tack (No.)		<b>5</b>	J. Dow Method

Item		Value	Test Method
Adhesion	JIS Method (N/10mm)	<b>7.0</b>	JIS Z 0237 (*1)

\*1 : JIS Z 0237 has been revised on Dec. 21<sup>st</sup>, 2009.

•Regard on the test method, please refer to "Label Materials Technical Information / About The Testing Method."

•The letter in front of the value stands for:

**B**: Base Material Failure, **Cf**: Cohesion Failure, **At**: Adhesive Transfer, **Zip**: Zipping, **NC**: Non Creep

•The above data is intended for informational and environmental safety purpose only, and do not constitute a guarantee or warranty of product performance. As performance may vary according to practices and conditions, sufficient prior testing is strongly recommended.

## <STORAGE>

•Avoid storage in places with high humidity and high temperature, and low temperature.

(Ideally store Temperature: 10°C~30°C, Humidity: less than 70%RH)

•At extreme condition, the adhesion and/or holding strength may deteriorate and become easier to peel off.

•Contact with water or chemical must be avoided, so polyethylene film packaging is recommended.

•Direct exposure to the sunlight must be avoided and a distance must be kept from the light source.

•To ensure a longer shelf life, store the rolls in a standing position and sheets in laying position and avoid causing any form of impact on the material.



Contacts: Printing & Variable Information  
 Products Operations  
 Overseas Div.

TEL.+81-3-3868-7734 FAX.+81-3-3868-7740

TEL.+81-3-3868-7730 FAX.+81-3-3868-7740

URL: <https://www.lintec-global.com/>